

**YN-X203-Y 3000W 20KHz** ■■■■






























**0000 - 9999**

| Month | Percentage |
|-------|------------|
| March | 75%        |
| April | 65%        |
| May   | 40%        |

 CE/FCC/ISO

**YN-X203-Y**

## Product Overview





## Specifications

| Parameter                         | Specification                                                                                                                                              |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div><div></div></div>            | 220V / 50Hz                                                                                                                                                |
| <div><div></div></div>            | 20KHz                                                                                                                                                      |
| <div><div></div></div>            | 3000W ( <div><div></div></div> 4000W / 6000W)                                                                                                              |
| <div><div></div></div>            | 0.35 – 20mm <sup>2</sup>                                                                                                                                   |
| <div><div></div></div>            | <div><div></div></div> <div><div></div></div> - <div><div></div></div>                                                                                     |
| <div><div></div></div>            | 0.5mm <sup>2</sup> – 35mm <sup>2</sup> ( <div><div></div></div> )                                                                                          |
| <div><div></div></div>            | <div><div></div></div> <div><div></div></div>                                                                                                              |
| <div><div></div><div></div></div> | <div><div></div></div>                                                                                                                                     |
| <div><div></div></div>            | 670 × 520 × 410mm                                                                                                                                          |
| <div><div></div></div>            | 88KG                                                                                                                                                       |
| <div><div></div></div>            | <div><div></div></div> 12 <div><div></div></div> / <div><div></div></div><br>( <div><div></div></div> + <div><div></div></div> ) 24 <div><div></div></div> |
| <div><div></div></div>            | CE / FCC / ISO9001                                                                                                                                         |

## Product Features

- [illegible]

## Applications

-   
  
  
  $\leq 100\mu\Omega$   
• 

IGBT 60%

- 

±0.05mm

- 

## Certifications

|     |     |     |    |     |     |     |      |
|-----|-----|-----|----|-----|-----|-----|------|
| CB  | 3C  | CQC | UL | FCC | CE  | GS  | UKCA |
| SAA | RCM | PSE | KC | KCC | NOM | BIS | BSMI |

**Winna | Yingna Technology**

Tel: +86 134 1065 0093

Email:  
liuyan@winna-group.com

WhatsApp: [wa.me/8613410650093](https://wa.me/8613410650093)

Web: [winna-group.com](http://winna-group.com)